Response to May 10, 2005 Final Office Action Application No. 10/075,183 Page 2

IN THE CLAIMS

1. (Currently Amended) A battery storage case including a main body having a first opening portion at one end of said main body and a bottom surface at an opposing end, and a lid portion having a second opening portion at one end of said lid portion and a head portion at an opposing end, said battery storage case comprising:

a first projection train formed on an outer surface of said main body near said first opening portion;

a second projection train formed on an outer surface of said main body near said bottom surface; and

a third projection train formed on an inner surface of said lid portion, wherein the third projection train is adapted to engage one of the first projection train and the second projection train, wherein a through-hole is formed through the head portion of said lid portion, and wherein the main body is capable of storing twice as many batteries when the third projection train engages the second projection train as opposed to when the third projection train engages the first projection train the main body is adapted to stores a battery having a length L, and wherein the distance between the first and second projection trains is equal to or greater than the length L of the battery.

- 2. (Previously Presented) The battery storage case according to claim 1, wherein said body portion of said main body and said body portion of said lid portion have cross-sections at least a part of which are shaped like a circular arc.
- 3. (Previously Presented) The battery storage case according to claim 2, wherein said main body and said lid portion have circular cross-sections.
- 4. (Previously Presented) The battery storage case according to claim 1 or 2, wherein said bottom surface is expanded toward the outside.

Response to May 10, 2005 Final Office Action

Application No. 10/075,183

Page 3

5. (Previously Presented) The battery storage case according to claim 1 or 2,

wherein said head portion has a space portion formed between said through-hole and said body

portion.

6. (Previously Presented) The battery storage case according to claim 1 or 2,

wherein a projection portion, the outside diameter of which is substantially the same as that of

said second opening portion, is formed on an outer surface of said body portion near said bottom

surface of said main body.

7. (Previously Presented) The battery storage case according to claim 1, wherein a

circumference portion of at least one opening portion of said through-hole is shaped like a

concave portion and a part of the circumference of said through-hole is shaped like a cylindrical

portion.

8. (Previously Presented) A battery storage case including a main body having a

first opening portion at one end and a bottom surface at the other end, and a lid portion having a

second opening portion at one end and a head portion at the other end, said battery storage case

comprising:

a first projection train formed on an outer surface of said main body near said bottom

surface;

a second projection train formed on an inner surface of said lid portion near said second

opening portion, wherein the second projection train is adapted to engage the first projection

train, and wherein the main body has a cross-section shaped as a pair of glasses.

9. (Previously Presented) The battery storage case according to claim 8, further

comprising a through-hole bored through the head portion of said lid portion.

Claims 10-11 (Cancelled)

Response to May 10, 2005 Final Office Action Application No. 10/075,183 Page 4

- 12. (Currently Amended) The battery storage case according to claim 8 or 10, wherein said bottom surface is expanded toward the outside.
- 13. (Previously Presented) The battery storage case according to claim 9, wherein said head portion has a space portion formed between said through-hole and a body portion of said lid portion.
- 14. (Currently Amended) The battery storage case according to claim 8 or 10, wherein a projection portion, the outside diameter of which is substantially the same as that of said second opening portion, is formed on an outer surface of said body portion near said bottom surface of said main body.
- 15. (Previously Presented) The battery storage case according to claim 9, wherein a circumference portion of at least one opening portion of said through-hole is shaped like a concave portion and a part of the circumference of said through-hole is shaped like a cylindrical portion.
- 16. (Previously Presented) A battery case including a main body having a first opening portion at one end and a bottom surface at the other end, and a lid portion having a second opening portion at one end and a head portion at the other end, said case comprising:
- a first projection train formed on said main body near said bottom surface; and a second projection train formed on said lid portion near said second opening portion, wherein the second projection train is adapted to engage the first projection train, and wherein the main body stores a battery.
- 17. (Previously Presented) The battery storage case according to claim 16, further comprising a through-hole bored through the head portion of said lid portion.

Response to May 10, 2005 Final Office Action Application No. 10/075,183

Page 5

18. (Previously Presented) The battery storage case according to claim 16, wherein said body portion of said main body and said body portion of said lid portion have cross-sections at least a part of which are shaped like a circular arc.

- 19. (Previously Presented) The battery storage case according to claim 16, wherein said main body and said lid portion have circular cross-sections.
- 20. (Previously Presented) The battery storage case according to claim 16 further comprising a third projection train formed on said main body near said bottom surface, wherein the second projection train is adapted to engage one of the first projection train and the third projection train.
- 21. (Previously Presented) The battery storage case according to claim 16, wherein the main body has a cross-section shaped as a pair of glasses.
- 22. (New) The battery storage case according to claim 1, wherein no projection trains are formed between first and second projection trains.
- 23. (New) The battery storage case according to claim 1, further comprising a stopper located between the first and second projection trains.